

Atrust

Atrust 14" Mobile Thin Client mt182L



1 Web Camera

Built-in web camera.

2 Power Button

Press to turn on the client.

3 Keyboard

Built-in keyboard for control and input.

4 Fingerprint Reader

Built-in fingerprint reader.

5 Speakers

Built-in Speaker for audio output.

6 Touchpad

Built-in pointing device for control and input.

7 DC IN

Connects to an AC adaptor.

8 HDMI

Connects to external display.

9 USB 3.1 Gen 1 Type-C

Connects to a USB device.

10 Audio Combo

Connects to a set of headphones system.

11 Kensington Lock Slot

Connects a Kensington cable to secure the mobile thin client.

12 USB 3.1 Gen 1 Type-C

Connects to a USB device.

13 USB 3.1 Gen 1 Type-A

Connects to a USB device.

14 USB 3.1 Gen 1 Type-A

Connects to a USB device.

Atrust mt182L Features

▼ **Low total cost of ownership**

Additional computing access is as simple as adding more thin client devices. The total cost of ownership is then drastically reduced.

▼ **Simple click and play**

Connects this device to the host server with a Remote Session connection. Just click the shortcut for a Remote Desktop session, you can immediately start a session and enjoy the computing resources.

▼ **Rich remote user experience**

Support Citrix® HDX/ICA™, Microsoft® RDP™ with RemoteFX™ and VMware® Horizon View™, this device can provide a rich and efficient computing experience.

▼ **Easy management and maintenance**

Since all computing tasks are mainly performed on a server, all hardware and software issues are significantly reduced on the client side. All user management, software installations, system management, and upgrades are done on a single server.



Atrust mt182L Mobile Thin Client

System	
Processor	Intel® Braswell Quad Core X5-E8000 1.04G(Burst to 2.0G)
Memory	
System memory	2GB (Manufacturing option: 4GB)
Flash memory	8GB (Manufacturing option: 32GB, 64GB)
Display	
LCD Type/Resolution	14" / 1920 x 1080 FHD
I/O Interfaces	
I/O ports	1 x HDMI, 2 x USB 3.1 Gen 1 Type-A, 2 x USB 3.1 Gen 1 Type-C, 1 x Audio Combo, 1 x DC IN, 1 x Fingerprint Reader, 1 x Web Camera, 2 x 2W Internal speaker, 1 x Internal microphone * USB3.1 Gen1 Type-C port did not support display function
Networking	
Ethernet	USB 3.1 to Gigabit Ethernet Adapter
Wireless	IEEE 802.11ac/a/b/g/n
Dimensions / Weight	
Dimensions	(W) 322 x (D) 222 x (H) 15.95 mm
Weight	1.2 kg (approximate)
Environment	
Operating temperature	5°C ~ 35°C
Non-operating temperature	-20°C ~ 60°C
Operating humidity (Rh)	10% ~ 90% (non-condensing)
Non-operating humidity (Rh)	5% ~ 95% (non-condensing)
AC Adaptor	
Operating voltage range	100 ~ 240 VAC
Rated line frequency	50 ~ 60 Hz
AC Adaptor	19V, 65W, 3.42A
Battery capacity	3290 mAh NOTE : The battery charges very slow under 10 degrees Celsius (50 degrees Fahrenheit) or above 35 degrees Celsius (95 degrees Fahrenheit). This is a natural limitation of battery cell technology. It is recommended to charge your battery above 10 degrees Celsius (50 degrees Fahrenheit) and under 35 degrees Celsius (95 degrees Fahrenheit). Note: Tolerance ±2°C

© 2021 Atrust Computer Corp. The information contained herein is subject to change without notice. Atrust shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are trademarks of the Microsoft group of companies. Citrix and ICA/HDX are trademarks of Citrix Systems, Inc.. VMware and Horizon View are trademarks of VMware, Inc.. To learn more, visit www.atrustcorp.com.