SEAL STORM
WATERPROOF MOUSE

Model: STM042(Black), STWM042(White), STM042RED(Red)

Seal Shield Washable, Waterproof Seal Storm Mouse has a 100% waterproof & dishwasher-safe rating that is IP68-certified and designed to withstand industrial-grade disinfectants and cleaners. A natural design stands up to frequent and vigorous cleaning. Features a convenient USB connection with RF shielding and Seal Cap™ protector for easy plug-and-play. PS/2 Compatible.

FEATURES:

IP68-Certified 100% Waterproof, Dishwasher-Safe & Fully Submersible

Gold Plated USB Cable with RF Shielding & a Seal Cap™ USB Protector

Compatible with Industrial-Grade Cleaners & Disinfectants

Two Button Mouse with Scroll Wheel

ABS Plastic with Silicone Scroll Wheel, Stainless Steel Screws & Non-Corrosive Components

STM042 (Black)

STWM042 (White)

STM042RED (Red)

ADVANCED CLEANING CAPABILITIES

· Dishwasher-Safe

Compatible with Spray & Wipe Disinfectant Products:

· Clorox Healthcare®

· Lysol®

· PDI Products

· Bleach, Ethanol, IPA, Quats, Citric Acid, & Hydrogen Peroxide, and Other Industrial-Grade Cleaners and Disinfectants

CLOROX
HEALTHCARE®
COMPATIBLE

SEAL SHIELD™

SEAL STORM
WATERPROOF MOUSE

Model: STM042(Black), STWM042(White), STM042RED(Red)

TECHNICAL DATA:

Compatibility:	Windows®, Mac iOS®
Construction:	ABS Plastic
Design:	2 Button with Scroll Wheel (clickable)
Net Dimension:	4.6 x 2.35 x 1.43 in (11.7 x 5.96 x 3.62 cm)
Gross Dimensions:	5.5 x 3.75 x 1.75 in (31 x 21 x 11 cm)
Net Weight:	0.286 lb (0.130kg)
Gross Weight:	0.363 lb (0.165kg)
Cable Length:	6 ft (1.83 m)
Connection Type:	Gold Plated USB PS/2 Compatible
Button Switch Force:	100 ± 20 gf
Button Switch Life Cycle:	>10 Million Clicks
Scroll Type:	Scroll Wheel
Resolution:	1000 DPI
Optical Technology:	LED
Operating Voltage:	5VDC
Operating Current:	60mA
Storage Temperature:	5° to 140° F (-15° to 60° C)
EMI - RFI:	Conforms to FCC Rules for Class B Device
Waterproof/Dustproof Ratings:	IP68, NEMA 4X
Approvals/Certifications:	FCC, CE, RoHS, WEEE, ICES-003, WHQL, RCM, REACH, Cal Prop 65 UKCA

CE FC RoHS

Limited 2-Year Warranty