















RT-401-IGEL

Reliable, stylish and efficient.

Our entry-level model, the Rangee RT-401, impresses with its cost-effective efficiency and attractive design. Equipped with solid technology, it offers a reliable solution for everyday tasks. Discover the optimal balance between affordability and performance for a smooth working environment.



Products			
	SKU	Operating system	
RT-401-IGEL	21119723-1	IGELOS preinstalled	
		(IGELOS licence not included)	

Technical specification RT-401-IGEL

System	
Processor	Intel J3710, 1,6 - 2,6 GHz
RAM	4GB DDR3 SO-DIMM
Flash	32GB SATA Flash
Graphic	
Maximum resolution	2 x 2560x1440@60Hz
	3 x 1920x1080@60Hz
Ports	1xDP,2xHDMI
Audio	
Ports	1 x 2 in1 Audio In-Out

 Interfaces

 USB
 4 x USB 2.0, 2 x USB 3.0

 COM
 1 x COM

Network

Ethernet 2 x 100/1000 Mbit LAN RJ/45 Ethernet

Wireless LAN Support for USB sticks

Device

Dimensions 134 x 126 x 22 mm

Weight 0,7kg

Cooling fanless, convection

Operating temperature 5°-95°C, non-condensing

Power supply external power supply 12V 1,5A

Power consumption 110-220V 6 Watt power consumption (idle)

Warranty 3 years Bring-In incl. Advance exchange, within the first month from purchase, extendable up to 5 years

VESA mount optionally available

Remote Management IGEL UMS

Operating System IGEL OS Linux Derivat

Front

01



Back

02



Vesa mount

03



FREE DEMO

RANGEE.COM/FREE-DEMO



Rangee GmbH Gut-Dämme-Str. 11 52070 Aachen

I Tel: +49 (0) 241 99 72 85 0

Fax: +49 (0) 241 99 72 85 9

https://www.rangee.com

General: info@rangee.com
Distribution: sales@rangee.com
Support: support@rangee.com

MILL