UA10 All in One THIN CLIENT

EASY TO DEPLOY AND MAINTAIN FOR A SEAMLESS WORK ENVIRONMENT



Optimize cost with plug-and-play function

The UA10 with Intel[®] Smart Display Module-Large is a hassle-free thin-client solution. Easyto-deploy and maintain design delivers a variety of functions while being effortless to manage, reducing business costs



Enhance visual experience with up to 2 multi-display

Design for users working in healthcare, finance, or public sector. UA10 supports up to 2 multidisplays with DP and DVI-D ports, improving functionality for the work environment



Built-in 5M webcam and dual microphones

Collaborate easily from home or in the office. UA10 keeps seamless online interaction with a 5M webcam and dual microphones



Broaden your view with a bezelless and ultra-thin design

Immersive your work in every detail. With a 23.8" FHD LCD bezel-free and ultra-thin design, every feature is viewed in enhanced depth for maximum concentration

Ultimate efficiency at any angle

Maximize comfort by placing your device at multiple angles. UA10 offers up to 90 degrees of portrait and landscape orientation, allowing work efficiently without distractions

Reduce electricity bill with energy-efficiency CPUs

UA10 is equipped with Intel[®] Celeron[®] Jasper Lake N5100, significantly saving electricity bills to meet limited corporate budgets

UA10 TC238-JL

Efficiency, Sustainability, and Optimization

Environment

| | Performance | Expandability | | | |
|-------------------------|---|------------------------|---|--|--|
| CPU | Intel [®] Jasper Lake N5100 processor supports up to 2.8GHz Burst frequency, Quad Core four threads | WiFi (Optional) | M.2 for WiFi module (E Key) 2 external antenna holes reserved | | |
| Memory | 4GB DDR4-2933MHz single channel | Storage | Onboard 8GB eMMC as default mSATA slot for SSD installation | | |
| Multiple Display | 23.8" full HD LCD, 1 DP 1.4, 1 DVI-D | LAN | RJ-45 10/100/1000Mbps | | |
| Display Resolution | Full HD on LCD, 4K 60Hz on connected displays (Max) | USB | 2 USB-A 2.0, 2 USB-A 3.2 Gen1 | | |
| Brightness (typical) | 250 cd/m ² typ. | Audio | Combo audio jack for headset & internal speakers | | |
| Viewing Angle | CR(>10):178/178 (V/H) typ. | Power | DC 19V/ 3.42A 65W power adapter | | |
| Graphic & Multimedia | Intel[®] 11th UHD Graphics 24EUs Full HD 5MP webcam with microphones HEVC, VP9, and AVC decode support | Mechanical Function | Tilt: -5°~23° Pivot (None): 90° Height Adjust (None): 110mm Swivel (None): -65/65° | | |

| Security Lock | Kensington lock slot | Cooling | Passive cooling | |
|------------------|---|--------------------------|-------------------------------|--|
| WoL | RJ45 LAN with standby power design supports Magic Packet wake-up event fTPM 2.0 | Operating Temperature | 0 °C to 35 °C, 32 °F to 95 °F | |
| | | Operating Humidity | 20% - 80% non-condensing | |

| TPM | | fTPM 2.0 | | Humidity | | |
|----------|---|--|---|----------|------------------------|---|
| Physical | 540 540 Warrar S-year You n | sion (w x h x d) & Weight x 433 x 48mm / (without foot stand) / 3.2K x 520 x 249mm / (with foot stand) / 5.6Kg nty Policy limited warranty, excluding components* nay find the detailed warranty policy via the ge of UltrArmor's official website | - | Contact | servio Visit | act Us ce@ultrarmor.com our website .ultrarmor.com |