CyberMed NB Series

Battery Powered Medical Computers















Main Features

- High Resolution LED Panel
- PCAP Multi-Touch Display
- IP65 Rated
- UL/cUL/IEC60601-1 Certified
- Antimicrobial* Housing
- Wide Viewing Angle
- 19", 20", 22" and 24" Screen Sizes available

Input/Output


I/O Ports	4x USB 3.0 ports 2x USB 2.0 ports 1x USB-C (11th gen) 1x RS232/422/485	1x HDMI – In (6th/7th gen) 1x HDMI – Out (6th/7th gen) 1x DP (11th gen) 1x 4Pin DIN power Jack
Audio	Line-out & Microphon	e Jack w/2-channel speakers


Technical Specifications

Display	24" & 22" ^: 1920x1080 16:9 250nits 178°/178° Viewing Angle 3000:1 Contrast Ratio	
	20" : 1600x900 16:9 250nits 170°/170° Viewing Angle 1000:1 Contrast Ratio	
	19" : 1280×1024 5:4 (4:3) 250nits 170°/170° Viewing Angle 1000:1 Contrast Ratio	
CPU Support	6th/7th/11th Generation Intel Core 3955U/i3/i5/i7 Processors with vPro Technology	
Memory	2x DDR4 2133/2400MHz 204-pin SO-DIMM sockets, populated up to 32GB	
Operating System	Windows 10/11, Windows IoT, Windows 8.1 (6th Gen only), Windows 7 (6th Gen only), Linux	
Video & Graphics	Intel HD Graphics 520	
Touch Screen	PCAP Multi-Touch with Optional Antiglare Technology	
Networking	1x Gigabit (Gbe) LAN Intel i219LM 1x Gigabit (Gbe) LAN Realtek RTL8111G	
DC Power Out	Optional: Power Module with 26 Watts of Power Available for External Devices	
Wireless	Intel Dual Band Wireless-AC 802.11 AC + Bluetooth 4.2	
Expansion Slots	1x mPCIe Half-size slot	
	1x M.2 E key short slot for PCIe or USB interface	
	1 x PCIe x8 slot (19" & 20" Only)	
HDD Support	2x 6Gbps Serial ATA III ports	
TPM	Version 2.0 Standard. Optional: Version 1.2	
Battery	24" & 22"^: 3 Hot Swap Batteries with up to 21 Hour Run Time**	
	20" & 19": 2 Hot Swap Batteries with up to 12 Hour Run Time**	
	** 1 year warranty. Cybernet strongly recommends replacing every 2 years.	
Power Supply	120W Medical Grade Power Supply. Input: Universal 100~240V AC, 50-60Hz.	
	Supports Output Range: DC18V-19V. 6.3A Adapters.	
	12V/24V Support with Optional DC Converter	
Waterproof	IP65 Sealed Front Bezel and IPX1 Back Cover	


^{*}Antimicrobial technology protects the housing of the computer & tablet. Cybernet makes no direct or implied claims to protecting users or providing other health benefits.


^ 22" Model is no longer available





CyberMed NB22[^]





CyberMed NB20

Mechanical & Environmental

Dimensions	CyberMed NB24: 23.50" x 14.80" x 2.10" (L,W,D) CyberMed NB22": 21.75" x 14.50" x 1.92" (L,W,D) CyberMed NB20: 20.35" x 14.37" x 1.95" (L,W,D) CyberMed NB19: 17.75" x 16.50" x 3.00" (L,W,D)	
Weight	CyberMed NB24: 17.75 lbs w/o batteries* 20.65 lbs w/3 batteries*	
	CyberMed NB22 [^] : 15.35 lbs w/o batteries* 18.35 lbs w/3 batteries*	
	CyberMed NB20: 13.25 lbs w/o batteries* 15.25 lbs w/2 batteries*	
	CyberMed NB19: 15.25 lbs w/o batteries* 17.25 lbs w/2 batteries*	
Wall Mount	Supports 75mm & 100mm VESA mounting holes	
Environment	Operating Temperature: 0°C~35°C	
Relative Humidity	10%~90% (non-condensing)	
Certifications	UL60601-1, cUL60601-1, IEC60601-1, EN60601-1, UL60950 electrical safety, FCC class B, CE, Energy	
	Star, RoHS, WEEE	
	*Weight of the base stand not included in totals ^ 22" Model is no longer available	

Optional Features

- Antiglare Touchglass
- 2D Barcode Scanner
- 5 Megapixel Webcam
- 3 Battery Multi-charge Station
- Reading Light (19" & 20" Models)
- DC Power Output for Peripherals
- Fingerprint Reader
- Integrated Imprivata SSO
 Certified RFID Reader
- Extended Warranties

